

June.2025

📍 ENTA Lighting(Shenzhen)Ltd

📍 Floor 1-4, No. 17, Zhulongtian Road, Shuitian Community, 4th Industrial Zone, Shiyan Street, Baoan District, Shenzhen


☎ 0755-36633250-8032

✉ tony@entaled.com

🌐 www.entaled.com

2004-2025

**ENTA 21st Anniversary
Luminating the Future**



» COMPANY Introduction

Established in 2004, ENTA Lighting(Shenzhen)LTD.is a specialized manufacturer of LED flexible strips and LED linear lighting products. We are primarily dedicated to the research, development, and manufacturing of high-end LED linear lighting, innovative intelligent lighting fixtures, and smart systems. ENTA has obtained ISO9001:2015 and 14001:2015 management system certifications, and our products have been certified by UL/CE and other authorities.

ENTA has registered its brand trademarks in multiple countries worldwide and has established offices in major cities across China, including Beijing, Shanghai, and Guangzhou. We have forged long-term and stable strategic partnerships with several globally renowned enterprises, leading to widespread product distribution and customer recognition worldwide.

ENTA, a team of seasoned experts in LED intelligent lighting design and development is assembled. Presently, our main focus lies in delivering comprehensive intelligent lighting solutions and supplying light fixtures for high-end hotels, premium office buildings, and upscale shopping malls. With a well-established logistics system, we ensure smooth supply channels. Additionally, our professional technical and sales teams are dedicated to providing free technical training and guidance, guaranteeing impeccable after-sales service. We uphold a development trajectory of "steadfast commitment to quality for a century" and adhere to a "triple innovation" approach encompassing product innovation, technological innovation, and management innovation. Enta Lighting places great emphasis on intellectual property construction and protection, boasting multiple independent invention patents. Our product design philosophy revolves around the core principle of "prioritizing the quality of light."

Qualifications and Certifications





Globally Popular



ENTA has 21 years development history in the field of LED lighting, and has accumulated rich product experience. ISO9001&14001 system for systematic and standardized management to ensure stable/reliable product quality and lead time. ENTA has established its own standardized laboratory to provide accurate product technical basis for product research and development, while establish the long term strategic partnership with many well-known brands.

Company Development Journey





»| Soft LED Stripe Lights-Smart Light Series

Advantages

- ◆ 24V output has been used for safety consideration
- ◆ 10M single end input LED strip light without wattage dropping from the beginning to the end
- ◆ Provide one LED one cutting to meet the special application site
- ◆ The product has been used Samsung LED chips with high-precision resistance design for excellent heat-dissipation and longer lifespan
- ◆ The main research and development of the invention of two-color extrusion while with IP65-IP68 waterproof performance lamp belt

Applications

- ◆ Products designed for customized integrated wall, ceiling application needs to create, fully meet the ceiling slot, auxiliary lighting, and widely to the home, office work, commercial hotels and other Spaces.





10M/2835 SMD/120LEDs

- Light with ultra-long design-10m/roll, single-end input, consistent light no invisible voltage dropping
- High CRI Ra>95, Red R9>90, and the excellent light consistency SDCM < 3
- Ultra-short cut at every 8.3mm, one light/one cut for flexible use
- Silicone two-color extrusion waterproof tube with ultra-thin end-plug design, perfect embedding with aluminum profiles
- Solderless connector to achieve any DIY application
- Dimmable with controllers



10M/Reel


Product Size (mm)




Product Parameter

LED Type:	SMD2835
Voltage:	DC24V
CRI:	Ra > 95
SDCM:	<3
CCT:	2700K/3000K/3500K/4000K/6500K
LED Qty:	120LEDs/m
Lumens Efficacy:	85Lm/w
Luminous Flux:	1105Lm/m
Wattage:	13W/m
Cut Size:	8.3mm
Length:	10M/Reel


Distribution Curve Flux




Recommended Profiles




Product Accessories




SMD-2PIN-10MM-A



SMD-2PIN-10MM-B



SMD-2PIN-10MM-C



SMD-2PIN-10MM-X



5M/2835 SMD/120LEDs

- Cost-effective configuration, suitable for various project needs
- High CRI Ra>95, Red R9>90, and the excellent light consistency SDCM < 3
- Ultra-short cut at every 8.3mm, one light/one cut for flexible use
- Silicone two-color extrusion waterproof tube with ultra-thin end-plug design, perfect embedding with aluminum profiles
- Solderless connector to achieve any DIY application
- Dimmable with controllers



5M/Reel


Product Size (mm)




Product Parameter

LED Type:	SMD2835
Voltage:	DC24V
CRI:	Ra > 95
SDCM:	<3
CCT:	2700K/3000K/3500K/4000K/6500K
LED Qty:	120LEDs/m
Lumens Efficacy:	85Lm/w
Luminous Flux:	1105Lm/m
Wattage:	13W/m
Cut Size:	8.3mm
Length:	5M/Reel


Distribution Curve Flux




Recommended Profiles




Product Accessories




SMD-2PIN-10MM-A



SMD-2PIN-10MM-B



SMD-2PIN-10MM-C



SMD-2PIN-10MM-X



5M/2835 SMD/120LEDs

- Light with ultra-long design-5M/roll, single-end input, consistent light no invisible voltage dropping
- High CRI Ra>95, Red R9>90, and the excellent light consistency SDCM < 3
- Ultra-short cut at every 8.3mm, one light/one cut for flexible use
- Silicone two-color extrusion waterproof tube with ultra-thin end-plug design, perfect embedding with aluminum profiles
- Solderless connector to achieve any DIY application
- Dimmable with controllers



5M/Reel


Product Size (mm)




Product Parameter

LED Type:	SMD2835
Voltage:	DC24V
CRI:	Ra > 95
SDCM:	<3
CCT:	2700K/3000K/3500K/4000K/6500K
LED Qty:	120LEDs/m
Lumens Efficacy:	85Lm/w
Luminous Flux:	510Lm/m
Wattage:	6W/m
Cut Size:	8.3mm
Length:	5M/Reel


Distribution Curve Flux




Recommended Profiles




Product Accessories




SMD-2PIN-5MM-A



SMD-2PIN-5MM-B



SMD-2PIN-5MM-C



SMD-2PIN-5MM-X



5M/2835 SMD/120LEDs

- Cost-effective configuration, suitable for various project needs
- High CRI Ra>95, Red R9>90, and the excellent light consistency SDCM < 3
- Ultra-short cut at every 16.6mm, one light/one cut for flexible use
- Silicone two-color extrusion waterproof tube with ultra-thin end-plug design, perfect embedding with aluminum profiles
- Solderless connector to achieve any DIY application
- Dimmable with controllers



5M/Reel


Product Size (mm)




Product Parameter

LED Type:	SMD2835
Voltage:	DC24V
CRI:	Ra > 95
SDCM:	<3
CCT:	2700K/3000K/3500K/4000K/6500K
LED Qty:	120LEDs/m
Lumens Efficacy:	90Lm/w
Luminous Flux:	630Lm/m
Wattage:	7W/m
Cut Size:	8.3mm
Length:	5M/Reel


Distribution Curve Flux




Recommended Profiles




Product Accessories




SMD-3PIN-8MM-A



SMD-3PIN-8MM-B



SMD-3PIN-8MM-C



SMD-3PIN-8MM-X



2835 SMD/120LED/10mm

- High quality flexible double-sided electroplated PCB board with high reflector
- Super high Ra>95, Red R9>90, and SDCM < 5 for the excellent light consistency
- 95lm/w 6leds/cut high density of lamp has been design to present the consistency light effect no obvious dark area
- Silicone two-color extrusion waterproof tube with ultra-thin end-plug design, perfect embedding with aluminum profiles
- Solderless connector to achieve any DIY application
- Dimmable with controllers



5M/Reel


Product Size (mm)




Product Parameter

LED Type:	SMD2835
Voltage:	DC24V
CRI:	Ra > 90
SDCM:	<5
CCT:	2700K/3000K/3500K/4000K/6500K
LED Qty:	120LEDs/m
Lumens Efficacy:	95Lm/w
Luminous Flux:	1425Lm/m
Wattage:	15W/m
Cut Size:	50mm/6Light
Length:	5M/Reel


Distribution Curve Flux



Recommended Profiles



Product Accessories





2835 SMD/140LED/10mm

- High quality flexible double-sided electroplated PCB board with high reflector
- Super high Ra>95, Red R9>90, and SDCM < 5 for the excellent light consistency
- 7leds/cut high density of lamp has been design to present the consistency light effect no obvious dark area
- Silicone two-color extrusion waterproof tube with ultra-thin end-plug design, perfect embedding with aluminum profiles
- Solderless connector to achieve any DIY application
- Dimmable with controllers



5M/Reel


Product Size (mm)




Product Parameter

LED Type:	SMD2835
Voltage:	DC24V
CRI:	Ra > 90
SDCM:	<5
CCT:	2700K/3000K/3500K/4000K/6500K
LED Qty:	140LEDs/m
Lumens Efficacy:	110Lm/w
Luminous Flux:	1650Lm/m
Wattage:	15W/m
Cut Size:	50mm/7Light
Length:	5M/Reel


Distribution Curve Flux



Recommended Profiles



Product Accessories





2835 SMD/70LED/8mm

- Cost-effective configuration, suitable for various project needs
- Super high Ra>95, Red R9>90, and SDCM < 5 for the excellent light consistency
- 100mm cutting distance, 7 lamps a cut, light efficiency 100LMW
- Silicone two-color extrusion waterproof tube with ultra-thin end-pull design, perfect embedding with aluminum profiles
- Solderless connector to achieve any DIY application
- Dimmable with controllers



5M/Reel


Product Size (mm)




Product Parameter

LED Type:	SMD2835
Voltage:	DC24V
CRI:	Ra > 90
SDCM:	<5
CCT:	2700K/3000K/3500K/4000K/6500K
LED Qty:	70LEDs/m
Lumens Efficacy:	100Lm/w
Luminous Flux:	1200Lm/m
Wattage:	12W/m
Cut Size:	100mm/7Light
Length:	5M/Reel


Distribution Curve Flux




Recommended Profiles




Product Accessories




SMD-2PIN-8MM-A



SMD-2PIN-8MM-B



SMD-2PIN-8MM-C



SMD-2PIN-8MM-X



2835 SMD/120LED/8mm

- High quality flexible double-sided electroplated PCB board with high reflector
- Super high Ra>95, Red R9>90, and SDCM < 5 for the excellent light consistency
- Glides/cut, high density of lamp has been designed to present the consistency light effect no obvious dark area
- Silicone two-color extrusion waterproof tube with ultra-thin end-pull design, perfect embedding with aluminum profiles
- Solderless connector to achieve any DIY application
- Dimmable with controllers



5M/Reel


Product Size (mm)




Product Parameter

LED Type:	SMD2835
Voltage:	DC24V
CRI:	Ra > 90
SDCM:	<5
CCT:	2700K/3000K/3500K/4000K/6500K
LED Qty:	120LEDs/m
Lumens Efficacy:	95Lm/w
Luminous Flux:	1140Lm/m
Wattage:	12W/m
Cut Size:	50mm/6Light
Length:	5M/Reel


Distribution Curve Flux




Recommended Profiles




Product Accessories




SMD-2PIN-8MM-A



SMD-2PIN-8MM-B



SMD-2PIN-8MM-C



SMD-2PIN-8MM-X



2835 SMD/140LED/8mm

- High quality flexible double-sided electroplated PCB board with high reflector
- Super high Ra>95, Red R9>90, and SDCM < 5 for the excellent light consistency
- 50mm cutting distance, 7 lamps a cut, light efficiency 110LM/W
- Silicone two-color extrusion waterproof tube with ultra-thin end-plug design, perfect embedding with aluminum profiles
- Solderless connector to achieve any DIY application
- Dimmable with controllers



5M/Reel


Product Size (mm)




Product Parameter

LED Type:	SMD2835
Voltage:	DC24V
CRI:	Ra > 90
SDCM:	<5
CCT:	2700K/3000K/3500K/4000K/6500K
LED Qty:	140LEDs/m
Lumens Efficacy:	110Lm/w
Luminous Flux:	1320Lm/m
Wattage:	12W/m
Cut Size:	50mm/7Light
Length:	5M/Reel


Distribution Curve Flux




Recommended Profiles




Product Accessories




SMD-2PIN-8MM-A



SMD-2PIN-8MM-B



SMD-2PIN-8MM-C



SMD-2PIN-8MM-X



2835 SMD/120LED/5mm

- High quality flexible double-sided electroplated PCB board with high reflector
- Super high Ra>95, Red R9>90, and SDCM < 5 for the excellent light consistency
- 50mm cutting distance, 6 lamps a cut, light efficiency 95LM/W
- Ultra-narrow width 5mm PCB design for met small size cabinet embedded demand
- Solderless connector to achieve any DIY application
- Dimmable with controllers



5M/Reel


Product Size (mm)




Product Parameter

LED Type:	SMD2835
Voltage:	DC24V
CRI:	Ra > 90
SDCM:	<5
CCT:	2700K/3000K/3500K/4000K/6500K
LED Qty:	120LEDs/m
Lumens Efficacy:	95Lm/w
Luminous Flux:	570Lm/m
Wattage:	6W/m
Cut Size:	50mm/6Light
Length:	5M/Reel


Distribution Curve Flux




Recommended Profiles




Product Accessories




SMD-2PIN-5MM-A



SMD-2PIN-5MM-B



SMD-2PIN-5MM-C



SMD-2PIN-5MM-X




»| Soft Light Stripe- Phantom Series

Advantages

- ◆ 24V output has been used for safety consideration
- ◆ High density of LED quantity design present super bright efficiency while no dark lighting effect
- ◆ Multi-color integrated design is to realize the application of multiple application
- ◆ Two-color extrusion invention patent invention technology with IP65 waterproof rate for any critical application
- ◆ The product can cooperate with intelligent controller to realize intelligent lighting

Applications

- ◆ The light stripe can be widely used in indoor and outdoor application, atmosphere lighting, landscape lighting, furniture, advertising and other supporting purposes





2835 SMD/120LED/10mm

- High quality flexible double-sided electroplated PCB board with high reflector
- Ra>90, R9>50, SDCM<5 for super uniform/excellent color
- 100mm Cutting distance, PCB Width 10mm, 12leds/cut, efficiency 95LM/W
- Multi CCT 2700K-6500K has been provided
- Solderless connector is provided for connection easily



5M/Reel


Product Size (mm)




Product Parameter

LED Type:	SMD2835
Voltage:	DC24V
CRI:	Ra > 90
SDCM:	<5
CCT:	2700K-6500K
LED Qty:	120LEDs/m
Lumens Efficacy:	90Lm/w
Luminous Flux:	900Lm/m
Wattage:	10W/m
Cut Size:	100mm/12Light
Length:	5M/Reel


Distribution Curve Flux



Recommended Profiles



Product Accessories





2835 SMD/140LED/8mm

- High quality flexible double-sided electroplated PCB board with high reflector
- Ra>90, R9>50, SDCM<5 for super uniform/excellent color
- 100mm Cutting distance, PCB Width 8mm, 14leds/cut, efficiency 110LM/W
- Multi CCT 2700K-6500K has been provided
- Solderless connector is provided for connection easily



5M/Reel


Product Size (mm)




Product Parameter

LED Type:	SMD2835
Voltage:	DC24V
CRI:	Ra > 90
SDCM:	<5
CCT:	2700K-6500K
LED Qty:	140LEDs/m
Lumens Efficacy:	100Lm/w
Luminous Flux:	1000Lm/m
Wattage:	10W/m
Cut Size:	100mm/14Light
Length:	5M/Reel


Distribution Curve Flux



Recommended Profiles



Product Accessories







5050RGB/60LED/10mm

- High quality flexible double-sided electroplated PCB board with high reflector
- Super high quality 5050 RGB has been used
- 100mm cutting distance, PCB Width 10mm, 6leds/cut
- Dimming in color/brightness is provided as option
- Solderless connector is provided for connection easily




Product Size (mm)




Product Parameter

LED Type:	5050RGB
Voltage:	DC24V
CRI:	/
SDCM:	/
CCT:	/
LED Qty:	60LEDs/m
Lumens Efficacy:	R:20, G:60, B:13 Lm/w
Luminous Flux:	R:80, G:240, B:54 Lm/m
Wattage:	12W/m
Cut Size:	100mm/6Light
Length:	5M/Reel


Recommended profiles




Product Accessories




SMD-4PIN-10MM-A



SMD-4PIN-10MM-B



SMD-4PIN-10MM-C



SMD-4PIN-10MM-X


5050RGBW/60LED/12mm

- High quality flexible electroplated copper double PCB for excellent quality
- 5050 RGBW 4 colors in one for excellent consistent CCT
- 100mm cutting distance, PCB Width 12mm, 6leds/cut
- Dimming in color/brightness is provided as option
- Solderless connector is provided for connection easily



5M/Reel


Product Size (mm)




Product Parameter

LED Type:	SMD5050
Voltage:	DC24V
CRI:	Ra > 90
SDCM:	<5
CCT:	RGB+3000K
LED Qty:	60LEDs/m
Lumens Efficacy:	W:60 Lm/w
Luminous Flux:	W:270 Lm/m
Wattage:	12W/m
Cut Size:	100mm/6Light
Length:	5M/Reel


Distribution Curve Flux



Recommended profiles



Product Accessories




5050RGBWC/60LED/12mm

- High quality flexible electroplated copper double PCB for excellent quality
- 5050 RGBWC 5 colors in one for excellent consistent CCT
- 100mm cutting distance, PCB Width 12mm, 6leds/cut
- Dimming in color/brightness is provided as option
- Solderless connector is provided for connection easily



5M/Reel


Product Size (mm)



Product Parameter

LED Type:	SMD5050
Voltage:	DC24V
CRI:	Ra > 90
SDCM:	<5
CCT:	RGB+2700K+6500K
LED Qty:	60LEDs/m
Lumens Efficacy:	W/C:60 Lm/w
Luminous Flux:	W/C:270 Lm/m
Wattage:	12W/m
Cut Size:	100mm/6Light
Length:	5M/Reel


Distribution Curve Flux



Recommended profiles




Product Accessories





5050RGB+2835/140LED/12mm

- High quality flexible electroplated copper double PCB for excellent quality
- Dual color high-lumen 5050RGB & SMD 2835LED is used for high efficiency
- 100mm cutting distance, 12mm width PCB, 35leds/cut
- Dimming in color/brightness is provided as option
- Solderless connector is provided for connection easily

5M/Reel




Product Size (mm)




Product Parameter

LED Type:	5050RGB+2835
Voltage:	DC24V
CRI:	Ra > 90
SDCM:	<5
CCT:	RGB+2700K+6500K
LED Qty:	140 LEDs/m
Lumens Efficacy:	W/C:100 Lm/w
Luminous Flux:	W/ C:600 Lm/m
Wattage:	W/ C:18W/m
Cut Size:	250mm/35Light
Length:	5M/Reel


Distribution Curve Flux




Recommended Profiles




Product Accessories




SMD-6PIN-12MM-A



SMD-6PIN-12MM-B



SMD-6PIN-12MM-C



SMD-6PIN-12MM-X



5050RGB /48LED/10mm

- High quality flexible electroplated copper double PCB for excellent quality
- 5050RGB addressable RGB IC design for super lighting effect
- 62.5mm cutting distance, PCB width 10mm, 3leds/cut
- SPI Controller for addressable, color fading, tracing lighting effect etc automatically
- Solderless connector is provided for connection easily

5M/Reel




Product Size (mm)




Product Parameter

LED Type:	5050RGB
Voltage:	DC12V
CRI:	/
SDCM:	/
CCT:	RGB
LED Qty:	48LEDs/m
Lumens Efficacy:	/
Luminous Flux:	/
Wattage:	6.6W/m
Cut Size:	62.5mm/3Light
Length:	5M/Reel


Recommended Profiles




Product Accessories




SMD-4PIN-10MM-A




SMD-4PIN-10MM-B



SMD-4PIN-10MM-C



SMD-4PIN-10MM-X



»| Neon Light Stripe-Smart Light Series

Advantages

- ◆ Bicolor, three-color integrated extrusion and cutting are clearly visible.
- ◆ High contrast is achieved with clear color indication. Four-step color tolerance ensures precise color matching.
The surface is refined with no blemishes, dirt-resistant and non-slippery.
- ◆ IP67 waterproof, UV-resistant, and salt spray resistant.
- ◆ Multiple installation methods are available, including snap-fit, keel, and profiles.

Application

- ◆ The product can be widely used in indoor lighting and furniture lighting atmosphere and surrounding lighting, and can be used in the installation of narrow spaces.




0306 Side-emitting Neon Light Stripe

- Three-color co-extruded 0306 single color or double- color multiple out-line style side-emitting light strip
- High CRI, SDCM<3, no light spots
- The appearance is exquisite,dirt-resistant and does not absorb dust
- IP67 waterproof,UVrisistant,and salt spray resistant

5M/Reel




Product Size (mm)



Product Parameter


LED Type:	Side-emitting neon light strip
Voltage:	DC24V
CRI:	Ra > 90
Dimming:	PWM Dimming
CCT:	2700K/3000K/3500K/4000K/5000K/2700K-6500K
LED Qty:	140LEDs/m
Lumens Efficacy:	23Lm/w
Luminous Flux:	230Lm/m
Wattage:	6W/m
Cut Size:	35mm(Single)/45mm(Dual)
Length:	5M/Reel




0612 Side-emitting Neon Light Stripe

- Three-color co-extruded 0306 single color or dual- color multiple out-line style side-emitting light strip
- High CRI, SDCM<3, no light spots
- The appearance is exquisite,dirt-resistant and does not absorb dust
- IP67 waterproof,UVrisistant,and salt spray resistant
- Multiple installation methods are available, including snap-fit, keel, and profile.

5M/Reel




Product Size (mm)





Product Parameter

LED Type:	Side-emitting neon light strip
Voltage:	DC24V
CRI:	Ra > 90
Dimming:	PWM Dimming
CCT:	2700K/3000K/3500K/4000K/6500K/2700K-6500K
LED Qty:	140LEDs/m
Lumens Efficacy:	35Lm/w
Luminous Flux:	420Lm/m
Wattage:	12W/m
Cut Size:	50mm
Length:	5M/Reel



Recommended Profiles




1010 Neon Light Stripe

- Three-color co-extrusion 1010 single-color or double-color, RGB group control, multiple wiring methods for positive light-emitting.
- LED stripes with high color rendering index, SDCM<3, no light spots. The appearance is exquisite, dirt-resistant, and does not absorb dust.
- IP67 waterproof, UV-resistant, salt spray resistant.
- Multiple installation methods are available, including snap-fit, keel, and profiles.



5M/Reel


Product Size (mm)





Product Parameter

LED Type:	1010 Neon Light Stripe
Voltage:	DC24V
CRI:	Ra > 90
Dimming:	PWM Dimming
CCT:	2700K/3000K/3500K/4000K/6500K/2700K-6500K
LED Qty:	140LEDs/m
Lumens Efficacy:	55Lm/w
Luminous Flux:	660Lm/m
Wattage:	12W/m
Cut Size:	50mm
Length:	5M/Reel

Distribution Curve Flux



Recommended Profiles




1616 Glowing Neon Light Stripe (single color, dual color)

- Three-color integrated extrusion and cutting are clearly visible. High contrast is achieved with clear color indication.
- Three-step color tolerance ensures precise color matching.
- The appearance is exquisite, dirt-resistant, and does not absorb dust.
- IP67 waterproof, UV-resistant, and salt spray resistant.



5M/Reel


Product Size (mm)





Product Parameter

LED Type:	1616 Neon Light Stripe
Voltage:	DC24V
CRI:	Ra > 90
Dimming:	PWM Dimming
CCT:	2700K/3000K/3500K/4000K/6500K/2700K-6500K
LED Qty:	140LEDs/m
Lumens Efficacy:	50Lm/w
Luminous Flux:	600Lm/m
Wattage:	12W/m
Cut Size:	50mm
Length:	5M/Reel

Distribution Curve Flux



Recommended Profiles




Ns1220 Side-emitting Neon Light Stripe(single-color dual-color)

- Triple-color co-extrusion 1220 single or dual color, RGB group control, straight-out line/bottom-out line, side-lit
- Light stripe with high color rendering index, SDCM<3, no light spots
- Exquisite appearance, dirt-resistant, dust-repellent
- IP67 waterproof, UV-resistant, salt spray-proof
- Multiple installation options available: clips, keel, profiles



5M/Reel


Product Size (mm)





Product Parameter

LED Type:	Side-emitting neon light strip
Voltage:	DC24V
CRI:	Ra > 90
Dimming:	PWM Dimming
CCT:	2700K/3000K/3500K/4000K/6500K/2700K-6500K
LED Qty's:	140LEDs/m
Lumens Efficacy:	55Lm/w
Luminous Flux:	660Lm/m
Wattage:	12W/m
Cut Size:	50mm
Length:	5M/Reel

Distribution Curve Flux



Recommended Profiles




1616 Neon Light Stripe (512/SPI)

- RGB Color-changing solution, RGB 512 solution, RGBW 512 solution
- Tri-Color co-extrusion with clear cutting marks high color rendering index
- Exquisite appearance, stain-resistant, dust-repellent
- IP67 waterproof, UV-resistant, salt spray resistant



5M/Reel


Product Size (mm)




Product Parameter

LED Type:	1616 Neon Light Stripe
Voltage:	DC24V
CRI:	Ra > 90
Dimming:	512/SPI
CCT:	RGB(SPI)/RGB(512)/RGBW(512)
LED Qty's:	60LEDs/m
Lumens Efficacy:	/
Luminous Flux:	/
Wattage:	14W/m / 18W/m
Cut Size:	100mm
Length:	5M/Reel

Distribution Curve Flux



Recommended Profiles







AC220V High-voltage Dual-color Temperature Flexible Light Stripe

- AC220V power supply, no driving power required, cost-saving;
- No controller needed, achieves color temperature switching between cool white and warm white through simple on/off operation of a regular switch;
- High thermal conductivity flexible circuit board design, bendable for easy installation;
- High-voltage constant current drive, minimal voltage drop, standard cascade up to 10 meters;
- IP65 silicone extrusion process, excellent waterproofing and safety performance;
- LED light source, energy-saving and eco-friendly, compliant with RoHS environmental standards.



5M/Reel


Product Size (mm)




Product Parameter

LED Type:	SMD2835
Voltage:	AC220V
CRI:	Ra > 90
SDCM:	<5
CCT:	2700K-6500K
LED Qty:	192LEDs/m
Lumens Efficacy:	64Lm/w
luminous flux:	700Lm/m
Wattage:	12W/m
Cut Size:	125mm/24LED
Length:	5M/Reel

Distribution Curve Flux



Product Accessories



Buckle


Nt 1004 Front Luminated Solid Extrusion Light Stripe (Monochrome/Bicolor)

- Solid extrusion produces monochromatic co-extruded 8mm wide panels with straight output lines, featuring integrated single-color extrusion for front-lit light strips and clearly visible cutting edges.
- High CRI, SDCM<3, no light spots
- Exquisite appearance, stain-resistant, and dust-repellent.
- IP68 waterproof rating, UV-resistant, and salt spray-proof.
- Multiple installation options available, including snap-fit and profile mounting.



5M/Reel


Product Size (mm)




Product Parameter

LED Type:	Nt 1004 Front Luminated Solid Extrusion Light Stripe
Voltage:	DC24V
CRI:	Ra > 90
Dimming:	PWM Dimming
CCT:	2700K/3000K/3500K/4000K/6500K/2700K-6500K
LED Qty:	140LEDs/m
Lumens Efficacy:	90Lm/w
Luminous Flux:	1080Lm/m
Wattage:	12W/m
Cut Size:	50mm
Length:	5M/Reel

Distribution Curve Flux



Recommended Profiles




NT 1204 Front Luminated Solid Extrusion Light Stripe(Monochrome/Bicolor)

- Solid extrusion produces single-color co-extruded 10mm wide panels with straight-out wiring, featuring integrated single-color extrusion for front-lit LED strips and clearly visible cutting.
- High thermal conductivity flexible circuit board design, bendable for easy installation;
- High CRI, SDCM<3, no light spots
- Exquisite appearance, stain-resistant, and dust-repellent.
- IP68 waterproof, UV-resistant, and salt spray-proof.
- Multiple installation options available, including snap-fit and profile mounting.



5M/Reel


Product Size (mm)




Product Parameter

LED Type:	Nt 1204 Front Luminated Solid Extrusion Light Stripe
Voltage:	DC24V
CRI:	Ra > 90
Dimming:	PWM Dimming
CCT:	2700K/3000K/3500K/4000K/6500K/2700K-6500K
LED Qty:	140LEDs/m
Lumens Efficacy:	90Lm/w
Luminous Flux:	1080Lm/m
Wattage:	12W/m
Cut Size:	50mm
Length:	5M/Reel

Distribution Curve Flux



Recommended Profiles





Flexible LED Wall Wash Stripe Light/Monochrome

- Optical design for multi beam angle options/wall washing
- Uniform in light. No stratified dark spots, multi-angle luminous wall washing.
- Same width of the lamp & end cap for elegant looking
- Flat bottom design for a variety of installation methods (back glue, silicone buckle etc)



5M/Reel


Product Size (mm)



Product Parameter

LED Type:	SMD2835
Voltage:	DC24V
CRI:	Ra > 90
SDCM:	<3
CCT:	2700K/3000K/4000K/6000K
LED Qty:	42LEDs/m
Lumens Efficacy:	95Lm/w
Luminous Flux:	1710Lm/m
Wattage:	18W/m
Cut Size:	166mm/7LED
Length:	5M/Reel

Distribution Curve Flux



Recommended Profiles



Silicone Clips



Stainless Clips


Flexible LED Wall Wash Stripe Light / Bicolor

- Optical design for multi beam angle options/wall washing
- Uniform in light. No stratified dark spots, multi-angle luminous wall washing.
- Same width of the lamp & end cap for elegant looking
- Multi CCT 2700K-6500K has been provided



5M/Reel


Product Size (mm)



Product Parameter

LED Type:	SMD2835
Voltage:	DC24V
CRI:	Ra > 90
SDCM:	<3
CCT:	2700K+6500K
LED Qty:	42LEDs/m
Lumens Efficacy:	95Lm/w
Luminous Flux:	1710Lm/m
Wattage:	18W/m(9W+9W)
Cut Size:	166mm/7LED
Length:	5M/Reel

Distribution Curve Flux



Recommended Profiles



Silicone Clips



Stainless Clips


0816 Flexible Wall Washer Lights (Monochrome/Bicolor)

- Dual-color co-extrusion 0816 single-color or dual-color, straight-out wire, side-out wire, front-emitting light stripe single-lamp single-cut
- High rendering index, sprayed with tactile on, no light spots
- Exquisite appearance, dirt-resistant, dust-proof
- P67 waterproof, UV-resistant, salt spray-proof
- Multiple installation options available, rotating buckle, fixed buckle.



1M/Reel


Product Size (mm)




Product Parameter

LED Type:	Front-emitting wall washer light
Voltage:	DC24V
CRI:	Ra > 90
Dimming:	RGBW(512 Solution)
CCT:	2700K/3000K/3500K/4000K/6500K/2700K-6500K
LED Qty:	18LEDs/m
Lumens Efficacy:	40Lm/w
luminous flux:	80Lm/m(40Lm/m+40Lm/m)
Wattage:	20W/m (10W/m+10W/m)
Cut Size:	55mm
Length:	1M/Reel

Distribution Curve Flux



Recommended Profiles



Fixed Installation



Rotational Installation


0816 Flexible Wall Washer Light(512 RGBW)

- Dual-color co-extrusion 0816 single-color or dual-color, RGBW512 color-changing solution, multiple wiring options for front-emitting light stripes individually cuttable
- High rendering index spray-coated with tactile on, no light spots
- Exquisite appearance, dirt-resistant, dust-repellent
- IP67 waterproof, UV-resistant, salt spray-proof
- Multiple Installation options available, rotating clips, fixed clips



1M/Reel


Product Size (mm)




Product Parameter

LED Type:	Front-emitting wall washer light
Voltage:	DC24V
CRI:	/
Dimming:	512 Dimming
CCT:	RGBW(512 Solution)
LED Qty:	18LEDs/m
Lumens Efficacy:	/
luminous flux:	/
Wattage:	30W/m
Cut Size:	55mm
Length:	1M/Reel

Distribution Curve Flux



Recommended Profiles





Fixed Installation






Rotational Installation

Single end punctured connector wired with cable

Image	Model	Code	Applicate light	Applicate PCB Width	Operating temperature	IP	Product size
	GF-SMD-2PIN-10MM-B	9130100010	monocolour	10mm	-20°C~+80°C	IP20	150*13.5*11.5
	GF-SMD-3PIN-10MM-B	9130100010	Two colors	10mm	-20°C~+80°C	IP20	150*13.5*11.5
	GF-SMD-4PIN-10MM-B	9130100010	RGB	10mm	-20°C~+80°C	IP20	150*13.5*11.5
	GF-SMD-5PIN-12MM-B	9130100010	RGBW	12mm	-20°C~+80°C	IP20	150*13.5*13.8
	GF-SMD-6PIN-12MM-B	9130100010	RGBCW	12mm	-20°C~+80°C	IP20	150*13.5*13.8

Double end punctured connector

Image	Model	Code	Applicate light	Applicate PCB Width	Operating temperature	IP	Product size
	GF-SMD-2PIN-10MM-B	9130100010	monocolour	10mm	-20°C~+80°C	IP20	13.5*11.5
	GF-SMD-3PIN-10MM-B	9130100010	Two colors	10mm	-20°C~+80°C	IP20	13.5*11.5
	GF-SMD-4PIN-10MM-B	9130100010	RGB	10mm	-20°C~+80°C	IP20	13.5*11.5
	GF-SMD-5PIN-12MM-B	9130100010	RGBW	12mm	-20°C~+80°C	IP20	13.5*13.8
	GF-SMD-6PIN-12MM-B	9130100010	RGBCW	12mm	-20°C~+80°C	IP20	13.5*13.8


FCOB Striplight-Single end punctured connector wired with cable

Image	Model	Code	Applicate light	Applicate PCB Width	Operating temperature	IP	Product size
	GF-COB-2PIN-8MM-B	9130100030	monocolour	8mm	-20°C~+80°C	IP20	150*13.5*9.8

FCOB Striplight-Double end punctured connector

Image	Model	Code	Applicate light	Applicate PCB Width	Operating temperature	IP	Product size
	GF-COB-2PIN-8MM-A	9130100040	monocolour	8mm	-20°C~+80°C	IP20	13.5*9.8

Single-end punctured connector wiring



Double-end punctured connector wiring

